

RAM 1500 CLASSIC SPECIFICATIONS

RAM 1500 CLASSIC TOWING—SAE J2807 COMPLIANT

Maximum Loaded Trailer Weight – kg (lb) When properly equipped			REGULAR CAB				QUAD CAB®		CREW CAB			
			6' 4" BOX		8' BOX		6' 4" BOX		5' 7" BOX		6' 4" BOX	
ENGINE	AXLE RATIO	GCWR ^x	4x2	4x4	4x2	4x4	4x2	4x4	4x2	4x4	4x2	4x4
3.6L PENTASTAR™ V6	3.21	4468 (9850)	2241 (4940)	2136 (4710)	2141 (4720)	2050 (4520)	2091 (4610)	1982 (4370)	2055 (4530)	1973 (4350)		
	3.55	5534 (12,200)	3307 (7290)	3202 (7060)								
	3.55	5625 (12,400)			3298 (7270)	3207 (7070)						
	3.55	5851 (12,900)					3475 (7660)	3366 (7420)	3438 (7580)	3357 (7400)		
5.7L HEMI® V8	3.21	6260 (13,800)	3924 (8650)	3832 (8450)	3824 (8430)	3738 (8240)	3783 (8340)	3701 (8160)	3760 (8290)	3670 (8090)	3738 (8240)	3656 (8060)
	3.92	6509 (14,350)	4173 (9200)	4082 (9000)								
	3.92	7189 (15,850)										4586 (10,110)
	3.92	7246 (15,975)			4813 (10,610)	4726 (10,420)	4772 (10,520)	4686 (10,330)	4745 (10,460)	4658 (10,270)	4726 (10,420)	

RAM 1500 CLASSIC PAYLOAD

Maximum Payload Capacities – kg (lb) When properly equipped		REGULAR CAB				QUAD CAB		CREW CAB			
		6' 4" BOX		8' BOX		6' 4" BOX		5' 7" BOX		6' 4" BOX	
ENGINE	GVWR ^x	4x2	4x4	4x2	4x4	4x2	4x4	4x2	4x4	4x2	4x4
3.6L PENTASTAR V6	2733 (6025)	685 (1510)									
	2858 (6300)		717 (1580)								
	2994 (6600)			866 (1910)	776 (1710)						
	3084 (6800)					875 (1930)	789 (1740)	848 (1870)	780 (1720)		
5.7L HEMI V8	2880 (6350)	730 (1610)	635 (1400)								
	2994 (6600)			762 (1680)	676 (1490)						
	3084 (6800)					776 (1710)	689 (1520)	748 (1650)	662 (1460)	730 (1610)	649 (1430)
	3130 (6900)					821 (1810)	735 (1620)	794 (1750)	708 (1560)	776 (1710)	694 (1530)

Notes regarding the charts above: numbers in **Black** boxes reflect max ratings. Payload and Max Trailer Weights are estimated values. All weights are shown in kg (lb) unless otherwise stated. Payload and Max Trailer Weight values are rounded to the nearest 4.5 kg (10 lb). Payload = GVWR – Base Weight. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807. Payload and Trailer Weight Rating are mutually exclusive. GAWRs, GVWRs and GCWRs should never be exceeded. The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV hitch receiver is limited to 499 kg (1,100 lb). Weight-distributing hitch is recommended for trailers over 2,268 kg (5,000 lb).

RAM 1500 CLASSIC INTERIOR DIMENSIONS

All dimensions are in millimetres (inches) unless otherwise noted	REGULAR CAB	QUAD CAB	CREW CAB
SEATING CAPACITY, FRONT / REAR	3 / 0 or 2 / 0	3 / 3 or 2 / 3	3 / 3 or 2 / 3
FRONT			
HEADROOM	1014 (39.9)	1041 (41)	1041 (41)
LEGROOM	1041 (41)	1041 (41)	1041 (41)
SHOULDER ROOM	1676 (66)	1676 (66)	1676 (66)
HIP ROOM	1599 (62.9)	1605 (63.2)	1605 (63.2)
REAR			
HEADROOM	N/A	1008 (39.7)	1014 (39.9)
LEGROOM	N/A	881 (34.7)	1023 (40.3)
SHOULDER ROOM	N/A	1669 (65.7)	1669 (65.7)
HIP ROOM	N/A	1598 (62.9)	1605 (63.2)
INTERIOR VOLUME			
FRONT – cu m (cu ft)	1.8 (62.5)	1.8 (64.2)	1.8 (64.2)
REAR – cu m (cu ft)	N/A	1.5 (52.4)	1.7 (61.1)
TOTAL PASSENGER VOLUME – cu m (cu ft)	1.8 (62.5)	3.3 (116.6)	3.5 (125.3)

N/A = Not applicable.

RAM 1500 CLASSIC EXTERIOR DIMENSIONS

All dimensions are for base models only and in inches (millimetres) unless otherwise noted	REGULAR CAB		QUAD CAB	CREW CAB	
	6' 4" BOX	8' BOX	6' 4" BOX	5' 7" BOX	6' 4" BOX
OVERALL BODY WIDTH	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)	2017.4 (79.4)
OVERALL HEIGHT (4x2 / 4x4)	1894.2 (74.6) / 1910.1 (75.2)	1889.2 (74.4) / 1095 (75)	1960.2 (77.2) / 1973.6 (77.7)	1953.3 (76.9) / 1967.9 (77.5)	1950.6 (76.8) / 1965.1 (77.4)
OVERALL LENGTH	5308.5 (209)	5866.5 (231)	5816.5 (229)	5816.5 (229)	6042.6 (237.9)
TRACK – FRONT (4x2 / 4x4)	1728.2 (68) / 1732.3 (68.2)	1728.2 (68) / 1732.3 (68.2)	1728.2 (68) / 1732.3 (68.2)	1728.2 (68) / 1732.3 (68.2)	1728.2 (68) / 1732.3 (68.2)
TRACK – REAR (4x2 / 4x4)	1714.9 (67.5) / 1714.9 (67.5)	1714.9 (67.5) / 1714.9 (67.5)	1714.9 (67.5) / 1714.9 (67.5)	1714.9 (67.5) / 1714.9 (67.5)	1714.9 (67.5) / 1714.9 (67.5)
WHEELBASE	3061 (120.5)	3569 (140.5)	3569 (140.5)	3569 (140.5)	3797 (149.5)
BED HEIGHT	511 (20.1)	513 (20.2)	511 (20.1)	509 (20)	511 (20.1)
BED LENGTH	1938 (76.3)	2497 (98.3)	1938 (76.3)	1712 (67.4)	1938 (76.3)
BED WIDTH, WALL-TO-WALL	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)	1687 (66.4)
BED WIDTH, BETWEEN WHEELHOUSINGS	1295 (51)	1295 (51)	1295 (51)	1295 (51)	1295 (51)
BED CARGO VOLUME – cu m (cu ft)	1.6 (57.5)	2.1 (74.7)	1.6 (57.5)	1.4 (50.3)	1.6 (57.5)

FOR FULL SPECIFICATIONS, VISIT [RAMTRUCK.CA/EN/BODY-BUILDER/GUIDE](https://ramtruck.ca/en/body-builder/guide)